



Bombardier Recreational Products
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



199 Extrusion Place
Hot Springs, AR 71901
501-262-5300 Phone
501-262-5053 Fax
www.xpressboats.com



2006 Xpress X-19

BOAT	
2006 Xpress X-19	
Material:	Aluminum
Length:	19'
Beam:	95"
Weight w/o Engine:	1225 LBS Dry
Maximum HP:	200 HP
Fuel Capacity:	30 Gallons
Transom height:	21" Shaft
Steering:	Hydraulic

ENGINE	
2006 Evinrude® 200 HP ETEC™ H.O.	
Engine Type:	90° V6
Horsepower:	Factory tuned
Displacement:	3.3 Litre
Induction:	ETEC DFI
Operating Range:	4500-5800 RPM
Weight:	509 LBS Dry Weight
Gear Ratio:	1.86:1

PROPELLER	
BRP Raker 2	
Material:	Stainless Steel
Diameter/Pitch:	14 1/2" x 28"
No. of Blades:	3
Part Number:	177009
MOUNTING HEIGHT	
Hole Position:	N/A
Jack Plate:	8" set back
AV Mounting:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	2.7	0.18	14.7	398
1000	5.4	1.03	5.3	143
1500	7.4	3.72	2.0	54
2000	15.1	5.17	2.9	79
2500	28.8	6.86	4.2	113
3000	36.5	8.67	4.2	114
3500	43.9	11.30	3.9	105
4000	50.8	14.43	3.5	95
4500	60.2	16.33	3.7	100
5000	68.0	18.25	3.7	101
5275	70.3	19.70	3.6	96
Range (Miles) Based on 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Rough
Wind Velocity:	25 MPH
Air Temperature:	88° F
Fuel Load:	30 Gallons Full
Weight:	2 Men (425 lbs.) Test Gear 20 lbs.

PERFORMANCE SUMMARY	
Top Speed:	70.3 MPH
Best Fuel Efficiency:	4.2 MPG with a range of 114 miles @ 36.5 MPH
Acceleration:	5.8 seconds to plane



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2005 BRP US Inc. All rights reserved.

™ ® Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

