



Bombardier Recreational Products
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



Wellcraft Marine Corp.
1651 Whitfield Avenue
Sarasota, FL 34243
(941) 753-7811 Fax 941-751-7808
www.wellcraft.com



2007 Wellcraft 212 Fisherman

BOAT	
2007 Wellcraft 212 Fisherman	
Material:	Fiberglass
Length:	20' 4"
Beam:	8' 10"
Weight w/o Engine:	2,750 LBS Dry
Maximum HP:	200 HP
Fuel Capacity:	77 Gallons
Transom height:	25" Shaft
Steering:	Hydraulic

ENGINE	
2007 Evinrude® 200 HP E-TEC®	
Engine Type:	90° V6
Horsepower:	200 HP @ 5250 RPM
Displacement:	158 CID
Induction:	E-TEC DFI
Operating Range:	4850-5850 RPM
Weight:	427 LBS Dry Weight
Gear Ratio:	1.85:1

PROPELLER	
BRP Viper	
Material:	Stainless Steel
Diameter/Pitch:	14 3/4" x 17"
No. of Blades:	3
Part Number:	176626
MOUNTING HEIGHT	
Hole Position:	#2
Jack Plate:	N/A
AV Mounting:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	1.9	0.18	10.6	732
1000	4.6	0.34	13.5	938
1500	6.4	1.58	4.1	282
2000	7.7	2.67	2.9	199
2500	8.7	4.33	2.0	138
3000	12.8	6.41	2.0	138
3500	24.9	6.62	3.8	261
4000	30.6	8.38	3.6	253
4500	34.9	10.60	3.3	228
5000	40.1	12.58	3.2	221
5500	44.1	15.44	2.9	198
5727	46.5	17.65	2.6	183
Range (Miles) based on 90% fuel tank				

TEST CONDITIONS	
Water Conditions:	Medium Chop
Wind Velocity:	ESE 5 to 8 MPH
Air Temperature:	85° F
Fuel Load:	77 Gallons Full
Weight:	2 Men (450 lbs.) Fuel, safety & test gear, 2 Group 27 Batteries

PERFORMANCE SUMMARY	
Top Speed:	46.5 MPH
Best Fuel Efficiency:	3.8 MPG with a range of 261 miles @ 24.9 MPH
Acceleration:	3.87 seconds to plane



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2006 BRP US Inc. All rights reserved.

™ ® Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

