

15 HP

Engine Model (Color)	(a) E15RG4 Graphite (b) E15RGL4 Graphite (c) E15TEG4 Graphite
Engine Type	2-cylinder
Bore x Stroke - in (mm)	2.4 x 2.36 (61 x 60)
Displacement - cu in (cc)	21.4 (351)
Gear Ratio	2.15:1
Full Throttle RPM Range	5000-6000 RPM
Weight - lbs (kg)*	(a) 114.4 (52) (b) 117 (53) (c) 120 (55)
Starting	(a)(b) Manual (c) Electric
Controls	Mechanical
Fuel Induction	Carbureted
Alternator Output	Only on Electric Models: 12V, 145W, 12A (optional on Electric Start Models)
Steering	(a)(b)(c) Tiller
Trim Method	Manual or Power Tilt
Shaft Length - in (mm)	(a)(c) 15 (381) (b) 20 (508)
Oil Tank Capacity - fl oz (ml)	32 (950)
Recommended Oil	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013 / CARB 3 STAR
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union

