

EVINRUDE® MULTI-FUEL ENGINE

30 MFE

SPECIFICATIONS

Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	2.992 x 2.5 (76 x 64)
Displacement - cu in (cc)	35 (575)
Gear Ratio	2.15:1
Full Throttle RPM Range	5500-6000 RPM
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	56 Amps Total / 15 Amps Net Dedicated
Trim Range	-5° to 15°
Tilt Range	65°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	1.5 (1.4)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane, JP5, JP8, Kerosene, Jet A, Jet B, and Diesel for Emergency
Warranty	1-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	STEERING	STARTING	TRIM METHOD	MODEL NO.	WEIGHT - lb (kg)
Tactical Black	20 (508)	Tiller	Electric/Rope	Manual Tilt	E30MRL	160 (73)

**NOT AVAILABLE FOR RECREATIONAL SALE.
ONLY AVAILABLE TO OFFICIAL MILITARY AGENCIES.**

* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp. Specifications subject to change.
©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

EVINRUDE®