

# EVINRUDE® MULTI-FUEL ENGINE

# 55 MFE

## SPECIFICATIONS

Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	3.62 x 2.60 (92 x 66)
Displacement - cu in (cc)	53 (864)
Gear Ratio	2.67:1
Full Throttle RPM Range	5500-6000 RPM
Starting	Rope (Electric Start Kit Available)
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	81 Amps Total / 25 Net Dedicated
Trim Method	Manual Tilt w/ assist cylinder
Trim Range	-5° to 15°
Tilt Range	68°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	2 (1.9)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane, JP5, JP8, Kerosene, Jet A, Jet B, and Diesel for Emergency
Warranty	1-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Tactical Black	20 (508)	Tiller	E55MRL	250 (113)
	20 (508)	Tiller	E55MJRL	277 (122)

**NOT AVAILABLE FOR RECREATIONAL SALE.  
ONLY AVAILABLE TO OFFICIAL MILITARY AGENCIES.**

\* Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp. Specifications subject to change.  
©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

**EVINRUDE®**