200 HP

SPECIFICATIONS

V6 66° E-TEC G2 D.I.
3.39 x 3.10 (86 x 78.7)
167 (2.6L)
2.17:1
5000-6000 RPM
Electric
ICON II Digital Shift and Throttle
E-TEC Direct Injection with Stratified Low RPM Combustion Mode
133 Total / 50 @ Wide Open Throttle / 14 @ Idle
Power Trim & Tilt
-6° to 15°
Multi-Point Targeted Oiling
On-Engine 3 (11.4) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
XPS Marine XD100
87 Octane
3-Year Engine** / 5-Year Corrosion
Minimum 26 (660)
Slate Gray or Classic White
Unlimited
Dual Axis Rigging / iTrim
EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - Ib (kg)	TILT RANGE
Single	Slate Gray	ay 20 (508)	iSteer DPS	C200GLF	530 (240)	81°
			Remote	C200GLP	496 (225)	75°
	Classic White	20 (508)	iSteer DPS	C200WLF	530 (240)	81°
			Remote	C200WLP	496 (225)	75°
Single [†] / Multiple	Slate Gray	25 (635)	iSteer DPS	C200GXF [†]	541 (245)	81°
			IHS / Tiebar	C200GXC [‡]	533 (242)	815
			Remote	C200GXP ⁺	507 (230)	75°
			Tiebar / Remote	C200GXCP [‡]	507 (230)	
			iDOCK	C200GXA	541 (245)	81°
			iDOCK	C200GXCA [‡]	533 (242)	
	Classic White		iSteer DPS	C200WXF [†]	541 (245)	81°
		25 (635)	IHS / Tiebar	C200WXC [‡]	533 (242)	01
			Remote	C200WXP [†]	507 (230)	75°
			Tiebar / Remote	C200WXCP [‡]	507 (230)	
			iDOCK	C200WXA	541 (245)	81°
			iDOCK	OCK C200WXCA‡ 533 (242)	01	

^{*} Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.





^{** 3} years of BRP Limited Warranty.

[†] Standard Rotation iSteer DPS and Remote models available for single and multiple installation. All iDOCK models available for multiple installation only.