

**EVINRUDE® E-TEC®**

**135 H.O.**



<b>Engine Model</b>	(a) E135HSL White (b) E135HGL Graphite (c) E135DHX White (d) E135HGX Graphite
<b>Engine Type</b>	V6 60° E-TEC D.I.
<b>Bore x Stroke - in (mm)</b>	3.62 x 2.60 (92 x 66)
<b>Displacement - cu in (cc) L</b>	158.2 (2592) 2.6L
<b>Gear Ratio</b>	(a)(b) 1.86:1 (c)(d) 1.85:1
<b>Full Throttle RPM Range</b>	5400-6000 RPM
<b>Weight - lbs (kg)</b>	(a)(b) 418 (190) (c)(d) 433 (196)
<b>Starting</b>	Electric
<b>Controls</b>	Mechanical (ICON EST Digital Accessory)
<b>Fuel Induction</b>	E-TEC Direct Injection with stratified low RPM combustion mode
<b>Alternator Output*</b>	133 Amps Total / 50 Net Dedicated
<b>Steering</b>	Remote
<b>Trim Method</b>	FasTrak™ Power Trim and Tilt
<b>Trim Range</b>	-6° to 15°
<b>Tilt Range</b>	75°
<b>Shaft Length - in (mm)</b>	(a)(b) 20 (508) (c)(d) 25 (635)
<b>Lubrication</b>	Multi-Point Targeted Oiling
<b>Oil Tank Capacity - gal (L)</b>	Accessory 1.8 (6.8) 3 (11.3) & 10 (37.85) Tank Available
<b>Recommended Oil</b>	Evinrude / Johnson XD-100 Oil
<b>Recommended Fuel</b>	87 Octane
<b>Counter Rotation</b>	N/A
<b>Warranty</b>	3-Year, Non-Declining
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR / European Union

\* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

