

# EVINRUDE® E-TEC® 25 HP



<b>Engine Model</b>	(a) E25DRS White (b) E25DRG Graphite (c) E25DRSL White (d) E25DRGL Graphite (e) E25DGTE Graphite (f) E25GTEL Graphite (g) E25DTSL White (h) E25DGTL Graphite (i) E25DPSL White (j) E25DPGL Graphite
<b>Engine Type</b>	Inline 2-Cylinder E-TEC D.I.
<b>Bore x Stroke - in (mm)</b>	2.992 x 2.5 (76 x 64)
<b>Displacement - cu in (cc) L</b>	35.2 (577)
<b>Gear Ratio</b>	2.15:1
<b>Full Throttle RPM Range</b>	5500-6000 RPM
<b>Weight - lbs (kg)</b>	(a)(b) 150 (68) (c)(d) 154 (70) (e) 162 (74) (f) 166 (75) (g)(h) 187 (85) (i)(j) 181 (82)
<b>Starting</b>	(a)(b)(c)(d) Rope (Electric Accessory) (e)(f)(g)(h)(i)(j) Electric and Rope
<b>Controls</b>	Mechanical
<b>Fuel Induction</b>	E-TEC Direct Injection with stratified low RPM combustion mode
<b>Alternator Output*</b>	56 Amps Total / 15 Amps Net Dedicated
<b>Steering</b>	(a)(b)(c)(d)(e)(f)(g)(h) Tiller (Remote Available) (i)(j) Remote (Tiller Available)
<b>Trim Method</b>	(a)(b)(c)(d)(e)(f) Manual Tilt (g)(h)(i)(j) Power Trim and Tilt
<b>Trim Range</b>	-4° to 16°
<b>Tilt Range</b>	65°
<b>Shaft Length - in (mm)</b>	(a)(b)(e) 15 (381) (c)(d)(f)(g)(h)(i)(j) 20 (508)
<b>Lubrication</b>	Multi-Point Targeted Oiling
<b>Oil Tank Capacity - gal</b>	1.7 (1.6)
<b>Recommended Oil</b>	Evinrude / Johnson XD-100 Oil
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	3-Year, Non-Declining
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR / European Union

\* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp.