

EVINRUDE® MULTI-FUEL ENGINE 30 MFE



Engine Model	E30MRL Tactical Black
Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	2.992 x 2.5 (76 x 64)
Displacement - cu in (cc) L	35.2 (577)
Gear Ratio	2.15:1
Full Throttle RPM Range	5500-6000 RPM
Weight - lbs (kg)	160 (73)
Starting	Electric/Rope
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	56 Amps Total / 15 Amps Net Dedicated
Steering	Tiller
Trim Method	Manual
Trim Range	-5° to 15°
Tilt Range	65°
Shaft Length - in (mm)	20 (508)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal	1.5 (1.4)
Recommended Oil	Evinrude / Johnson XD-100 Oil
Recommended Fuel	87 Octane, JP5, JP8, Kerosene, Jet A, Jet B, and Diesel for Emergency
Warranty	1-Year, Non-Declining

* Dry weight for the lightest model/version of each engine listed in that grouping.

** Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp.

**NOT AVAILABLE FOR RECREATIONAL SALE.
ONLY AVAILABLE TO OFFICIAL MILITARY AGENCIES.**