

EVINRUDE® E-TEC® G2®

175 HP

SPECIFICATIONS

Engine Type	V6 66° E-TEC G2 D.I.
Bore x Stroke - in (mm)	3.39 x 3.10 (86 x 78.7)
Displacement - cu in (L)	167 (2.7)
Gear Ratio	2.17:1
Full Throttle RPM Range	5000-6000 RPM
Starting	Electric
Controls	ICON II
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	133 Amps Total / 50 net Dedicated / 14 amps @ idle
Trim Method	Power Trim & Tilt
Trim Range	-6° to 15°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	On-Engine 3 (11.4) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
Recommended Oil	XPS Marine XD100
Recommended Fuel	87 Octane
Warranty	5-Year Engine** / 5-Year Corrosion
Mounting Centers - in (mm)	Minimum 26 (660)
Color Customization	Over 400 Color Panel Options
Integrated Features	Dual Axis Rigging / iTrim
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)	TILT RANGE	STEERING ANGLE
Single	Slate Gray	20 (508)	iSteer DPS	C175GLF	530 (240)	81°	+/- 30°
			Remote	C175GLP	496 (225)	75°	+/- 32°
	Classic White	20 (508)	iSteer DPS	C175WLF	530 (240)	81°	+/- 30°
			Remote	C175WLP	496 (225)	75°	+/- 32°
Single / Multiple	Slate Gray	25 (635)	iSteer DPS	C175GXF†	541 (245)	81°	+/- 30°
			IHS / Tiebar	C175GXC‡	533 (242)		
			Remote	C175GXP†	507 (230)		
	Classic White	25 (635)	Tie Bar/Remote	C175GXCP‡	512 (233)	75°	+/- 32°
			iSteer DPS	C175WXF†	541 (245)	81°	+/- 30°
			IHS / Tiebar	C175WXC‡	533 (242)		
Remote	C175WXP†	507 (230)					
Tie Bar/Remote	C175WXCP‡	512 (233)	75°	+/- 32°			

* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

** 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

† Standard Rotation iSteer DPS and Remote models available for single and multiple installation.

‡ Corresponding Counter Rotation model.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

EVINRUDE®