

EVINRUDE

E-TEC

PERFORMANCE REPORT

BULLETIN #: 1331
ENGINE 1: H200HGLF

BOAT TYPE: Aluminum

DATE OF TEST: 8/22/2019



BRP US, Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com

ALUMACRAFT
FAMILIES. FISHING. FOREVER. EST. 1948

Alumacraft
1329 N. 10th St
Arkadelphia, AR 71923
870-246-5555
www.alumacraft.com

2020 Alumacraft Pro 200

BOAT	
2020 Alumacraft Pro 200	
Material	Aluminum
Length	20'
Beam	98"
Weight w/o Engine	1745 lbs
Maximum HP	200 HP
Fuel Capacity	30 Gallons
Transom Height	21"
Steering	DPS

ENGINE	
Evinrude® E-TEC® G2™ 200 H.O. HP	
Engine Type	74° V-6
Horsepower	200 H.O.
Displacement	3.4 L
Induction	E-TEC DI
Operating Range	5400-6000 RPM
Weight	537 LBS Dry Weight
Gear Ratio	1.85:1

PROPELLER	
Rx4™	
Material	Stainless Steel
Diameter/Pitch	15 in x 22 in
No. of Blades	4
Part Number	177324
Prop Vent Hole	NA
MOUNTING HEIGHT	
Hole Position	#1
Jack Plate	Hydraulic

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	3.05	0.30	10.17	275
1000	5.95	0.80	7.44	201
1500	7.15	1.80	3.97	107
2000	8.15	3.55	2.30	62
2500	25.15	4.15	6.06	164
3000	33.10	5.90	5.61	151
3500	38.55	7.55	5.11	138
4000	44.45	10.60	4.19	113
4500	49.05	13.30	3.69	100
5000	54.55	15.55	3.51	95
5500	57.30	17.40	3.29	89

TEST CONDITIONS	
Water Conditions	Calm (rippled)
Wind Velocity	5 MPH
Air Temperature	82 ° F
Fuel Load	30 Gallons
Weight	Two men plus safety gear

PERFORMANCE SUMMARY	
Top Speed	57.3 MPH
Best Fuel Efficiency	6.06 MPG For 164 Miles @ 25.15 MPH
Acceleration	Zero to 20 MPH 3.48 Seconds

Fuel Data Range (Miles) Based On 90% Fuel Capacity



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 Gauges. Test performed and certified by BRP OEM Applications Engineering.

© 2019 BRP US Inc. All rights reserved. ™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

EVINRUDE