



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



Alumacraft Boat Co.
315 W. Saint Julien St.
St Peter, MN 56082
1-877-314-7756
www.alumacraft.com



2013 Alumacraft Water Fowler 16

BOAT	
2013 Alumacraft Water Fowler 16	
Material:	Aluminum
Length:	16'
Beam:	65"
Weight w/o Engine:	555 LBS Dry
Maximum HP:	40 HP
Fuel Capacity:	6 Gallons Portable
Transom Height:	20" Shaft
Steering:	Tiller

ENGINE	
2013 Evinrude® 25 HP ETEC®	
Engine Type:	In Line 2 Cyl
Horsepower:	25 HP @ 5500 RPM
Displacement:	32 Cu In
Induction:	ETEC DFI
Operating Range:	5500-6000 RPM
Weight:	162 LBS Dry Weight
Gear Ratio:	2.15:1

PROPELLER	
BRP	
Material:	Aluminum
Diameter/Pitch:	10.9 x 12"
No. of Blades:	3
Part Number:	177245
MOUNTING HEIGHT	
Hole Position:	On Transom
Jack Plate:	N/A
AV Mounting:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
750	1.9	0.07	26.4	143
1000	2.8	0.11	25.5	137
1500	3.8	0.19	20.0	108
2000	4.9	0.31	15.8	85
2500	5.9	0.51	11.6	62
3000	7.0	0.80	8.8	47
3500	10.0	1.09	9.1	49
4000	16.2	1.25	13.0	70
4500	20.0	1.52	13.1	71
5000	23.1	1.85	12.5	67
5500	26.4	2.19	12.1	65
5700	27.5	2.34	11.7	63

Range (Miles) Based On 90% Fuel Capacity

TEST CONDITIONS	
Water Conditions:	Calm
Wind Velocity:	5-10 MPH
Air Temperature:	82° F
Fuel Load:	Full
Weight:	1 Man, Fuel, Safety/Test Gear

PERFORMANCE SUMMARY
Top Speed: 27.5 MPH
Best Fuel Efficiency: 13.1 MPG with a range of 71 Miles @ 20.0 MPH
Acceleration: 3.7 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2011 BRP US Inc. All rights reserved.

™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

