



Bombardier Recreational Products Inc.  
10101 Science Drive  
Sturtevant, WI 53177  
[www.evinrude.com](http://www.evinrude.com)



Nautic Global Group  
4500 Middlebury Street  
Elkhart, IN 46516  
574-522-8381  
[www.aquapatioboats.com](http://www.aquapatioboats.com)



### 2013 Aqua Patio AP 220

| BOAT                   |              |
|------------------------|--------------|
| 2013 Aqua Patio AP 220 |              |
| Material:              | Aluminum     |
| Length:                | 23' 1"       |
| Beam:                  | 8' 6"        |
| Weight w/o Engine:     | 3078 LBS Dry |
| Maximum HP:            | 200 HP       |
| Fuel Capacity:         | 30 gallons   |
| Transom Height:        | 20" Shaft    |
| Steering:              | Hydraulic    |

| ENGINE                      |                    |
|-----------------------------|--------------------|
| 2013 Evinrude® ETEC® 150 HP |                    |
| Engine Type:                | 60° V6             |
| Horsepower:                 | 150 HP @ 5350 RPM  |
| Displacement:               | 158 Cu In          |
| Induction:                  | ETEC DFI           |
| Operating Range:            | 4850-5850 RPM      |
| Weight:                     | 418 LBS Dry Weight |
| Gear Ratio:                 | 1.86:1             |

| PROPELLER       |                 |
|-----------------|-----------------|
| BRP Viper™      |                 |
| Material:       | Stainless Steel |
| Diameter/Pitch: | 14 3/4" x 16"   |
| No. of Blades:  | 3               |
| Part Number:    | 763912          |
| MOUNTING HEIGHT |                 |
| Hole Position:  | #2              |
| Jack Plate:     | N/A             |
| Motor Height    | N/A             |

| PERFORMANCE DATA                         |             |             |            |            |
|--|-------------|-------------|------------|------------|
| RPM                                      | MPH         | GPH         | MPG        | RANGE      |
| 500                                      | 2.0         | 0.18        | 10.8       | 293        |
| 1000                                     | 4.0         | 0.50        | 7.9        | 213        |
| 1500                                     | 5.5         | 1.10        | 5.0        | 134        |
| 2000                                     | 7.0         | 1.95        | 3.6        | 96         |
| 2500                                     | 9.3         | 3.30        | 2.8        | 76         |
| <b>3000</b>                              | <b>16.8</b> | <b>4.40</b> | <b>3.8</b> | <b>103</b> |
| 3500                                     | 21.2        | 5.95        | 3.6        | 96         |
| 4000                                     | 27.6        | 7.65        | 3.6        | 97         |
| 4500                                     | 33.6        | 10.05       | 3.3        | 90         |
| 5000                                     | 37.8        | 12.35       | 3.1        | 83         |
| 5500                                     | 41.7        | 14.20       | 2.9        | 79         |
| 5700                                     | 42.3        | 15.10       | 2.8        | 76         |
| Range (Miles) Based On 90% Fuel Capacity |             |             |            |            |

| TEST CONDITIONS   |                                 |
|-------------------|---------------------------------|
| Water Conditions: | Calm                            |
| Wind Velocity:    | 5 MPH                           |
| Air Temperature:  | 73° F                           |
| Fuel Load:        | 1/2 Full                        |
| Weight:           | 1 Man, Fuel, test & safety gear |

| PERFORMANCE SUMMARY   |   |
|-----------------------|---|
| Top Speed:            | <b>42.3 MPH</b>                                     |
| Best Fuel Efficiency: | <b>3.8 MPG with a range of 103 Miles @ 16.8 MPH</b> |
| Acceleration:         | <b>3.1 seconds to plane</b>                         |

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2010 BRP US Inc. All rights reserved.

™ and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

