



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



Nauti Global Group
4500 Middlebury Street
Elkhart, IN 46516
574-522-8381
www.aquapatioboats.com



2013 Aqua Patio 240

BOAT	
2013 Aqua Patio 240	
Material:	Aluminum
Length:	25' 9"
Beam:	8' 6"
Weight w/o Engine:	2421 LBS Dry
Maximum HP:	300 HP
Fuel Capacity:	46 gallons
Transom Height:	25" Shaft
Steering:	Hydraulic/Electric

ENGINE	
2013 Evinrude® ETEC® 150HP	
Engine Type:	60° V6
Horsepower:	150 @ 5350 RPM
Displacement:	158 Cu In
Induction:	ETEC DFI
Operating Range:	4850-5850 RPM
Weight:	418 LBS Dry Weight
Gear Ratio:	1.86:1

PROPELLER	
BRP SSP™	
Material:	Stainless Steel
Diameter/Pitch:	15 5/8 x 13"
No. of Blades:	3
Part Number:	763960
MOUNTING HEIGHT	
Hole Position:	#2
Jack Plate:	N/A
Motor Height	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	1.9	0.18	10.5	434
1000	4.1	0.59	6.9	287
1500	5.9	1.18	5.0	206
2000	7.0	1.85	3.8	157
2500	13.1	3.23	4.0	167
3000	16.7	4.34	3.9	160
3500	21.3	6.22	3.4	142
4000	24.4	7.91	3.1	128
4500	27.9	10.63	2.6	109
5000	30.7	12.77	2.4	99
5500	34.1	15.00	2.3	94
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Heavy Chop
Wind Velocity:	15 MPH
Air Temperature:	82° F
Fuel Load:	1/4 Full
Weight:	2 Men, Fuel, test & safety gear

PERFORMANCE SUMMARY	
Top Speed:	34.1 MPH
Best Fuel Efficiency:	4.0 MPG with a range of 167 Miles @ 13.1 MPH
Acceleration:	4.5 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2010 BRP US Inc. All rights reserved.

™ and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

