



BULLETIN#: PE960

ENGINE: E250HSX

BOAT TYPE: Pontoon

DATE OF TEST: 8/28/12



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



Nauti Global Group
4500 Middlebury Street
Elkhart, IN 46516
574-522-8381
www.aquapatioboats.com



2013 Aqua Patio 240

BOAT	
2013 Aqua Patio 240	
Material:	Aluminum
Length:	25' 9"
Beam:	8' 6"
Weight w/o Engine:	2421 LBS Dry
Maximum HP:	300 HP
Fuel Capacity:	46 gallons
Transom Height:	25" Shaft
Steering:	Hydraulic/Electric

ENGINE	
2013 Evinrude® ETEC® 250HO	
Engine Type:	90° V6
Horsepower:	Factory Tuned
Displacement:	3.4 litre
Induction:	ETEC DFI
Operating Range:	4500-6000 rpm
Weight:	503 LBS Dry Weight
Gear Ratio:	1.85:1

PROPELLER	
BRP Viper™	
Material:	Stainless Steel
Diameter/Pitch:	14 3/4" x 17"
No. of Blades:	3
Part Number:	763914
MOUNTING HEIGHT	
Hole Position:	#2
Jack Plate:	N/A
Motor Height	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	1.9	0.21	9.3	383
1000	4.4	0.66	6.7	276
1500	6.1	1.40	4.4	181
2000	8.6	2.65	3.2	134
2500	12.6	5.96	2.1	88
3000	17.0	6.73	2.5	105
3500	21.5	8.21	2.6	108
4000	25.4	10.05	2.5	105
4500	30.8	12.57	2.4	101
5000	36.1	16.24	2.2	92
5500	40.2	21.76	1.8	76
6000	45.7	25.22	1.8	75
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Heavy Chop
Wind Velocity:	15 MPH
Air Temperature:	82° F
Fuel Load:	1/4 Full
Weight:	2 Men, Fuel, test & safety gear

PERFORMANCE SUMMARY	
Top Speed:	45.7 MPH
Best Fuel Efficiency:	2.6 MPG with a range of 108 Miles @ 21.5 MPH
Acceleration:	3.2 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2010 BRP US Inc. All rights reserved.

™ and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

