

EVINRUDE

E-TEC

PERFORMANCE REPORT

BULLETIN #: 1121 **ENGINE:** E250LH **BOAT TYPE:** Pontoon **DATE OF TEST:** 8/16/2014



BRP US, Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com



JC Manufacturing, Inc.
7248 St Road 13 N.
North Webster, IN 46555
574-834-2881
www.icpontoon.com

2015 JC Pontoon SportToon 24TT

BOAT	
2015 JC Pontoon SportToon 24TT	
Material	Aluminum
Length	24' 7"
Beam	8' 6"
Weight w/o Engine	2340 LBS
Maximum HP	250 HP
Fuel Capacity	45 Gallons
Transom Height	20"
Steering	DPS

ENGINE	
2015 Evinrude® E-TEC® G2™ 250 H.O.	
Engine Type	74° V-6
Horsepower	250 HP @ 5750 RPM
Displacement	3.4 Liter
Induction	E-TEC DFI
Operating Range	5400-6000 RPM
Weight	537 LBS Dry Weight
Gear Ratio	1.85:1

PROPELLER	
Evinrude® Rebel™	
Material	Stainless
Diameter/Pitch	15 3/8" X 18"
No. of Blades	3
Part Number	763988
MOUNTING HEIGHT	
Hole Position	#2
Jack Plate	No
AV Mounting	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	2.35	0.20	11.75	476
1000	4.55	0.70	6.50	263
1500	6.85	1.30	5.27	213
2000	8.10	2.45	3.31	134
2500	14.15	3.45	4.10	166
3000	21.75	6.45	3.37	137
3500	27.90	7.85	3.55	144
4000	33.55	10.10	3.32	135
4500	38.50	12.45	3.09	125
5000	44.00	15.80	2.78	113
5500	47.30	19.15	2.47	100
5800	50.50	21.80	2.32	94

TEST CONDITIONS	
Water Conditions	Lite chop
Wind Velocity	0-5 MPH
Air Temperature	60° F
Fuel Load	30 Gallons
Weight	1 Person/test and safety gear

PERFORMANCE SUMMARY	
Top Speed	50.5 MPH
Best Fuel Efficiency	3.55 MPG For 144 Miles @ 27.9MPH
Acceleration	3 seconds to plane

Fuel Data Range (Miles) Based On 90% Fuel Capacity



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2014 BRP US Inc. All rights reserved. ™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

EVINRUDE
E-TEC

