

EVINRUDE

E-TEC

PERFORMANCE REPORT

BULLETIN #: 1334
ENGINE 1: C150HGXA

BOAT TYPE: Pontoon

DATE OF TEST: 9/21/2019



BRP US, Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com

Manitou

Manitou
16020 S Lowell Rd.
Lansing, MI 48906
517-322-3822
www.manitoupontoonboats.com

2020 Manitou Oasis

BOAT	
2020 Manitou Oasis	
Material	Aluminum
Length	26'4"
Beam	8'6"
Weight w/o Engine	3305 lbs
Maximum HP	150 HP
Fuel Capacity	45 Gallons
Transom Height	25
Steering	DPS

ENGINE	
Evinrude® E-TEC® G2™ 150 H.O. HP	
Engine Type	66° V-6
Horsepower	150 H.O.
Displacement	2.7 L
Induction	E-TEC DI
Operating Range	5000-6000 RPM
Weight	541 LBS Dry Weight
Gear Ratio	2.16:1

PROPELLER	
Rebel™ TBX™	
Material	Stainless Steel
Diameter/Pitch	15 1/2 in x 17 in
No. of Blades	3
Part Number	763986
Prop Vent Hole	NA
MOUNTING HEIGHT	
Hole Position	#2
Jack Plate	None

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	1.95	0.20	9.75	395
1000	4.00	0.60	6.67	270
1500	6.15	1.20	5.13	208
2000	7.85	1.95	4.03	163
2500	9.45	2.70	3.50	142
3000	14.25	4.00	3.56	144
3500	18.35	5.20	3.53	143
4000	21.75	7.30	2.98	121
4500	25.85	9.40	2.75	111
5000	30.35	12.10	2.51	102
5200	30.85	12.10	2.55	103

TEST CONDITIONS	
Water Conditions	Slight Chop - 1' to 4'
Wind Velocity	15 MPH
Air Temperature	71 ° F
Fuel Load	43 Gallons
Weight	2 men & test gear

PERFORMANCE SUMMARY	
Top Speed	30.9 MPH
Best Fuel Efficiency	3.56 MPG For 144 Miles @ 14.25 MPH
Acceleration	Zero to 20 MPH 5.18 Seconds

Fuel Data Range (Miles) Based On 90% Fuel Capacity



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 Gauges. Test performed and certified by BRP OEM Applications Engineering.

© 2019 BRP US Inc. All rights reserved. ™ ® and the BPR logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

EVINRUDE