



BULLETIN #: PE931

ENGINE: E150DSLAA

BOAT TYPE: Pontoon

DATE OF TEST: 7/24/12



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com



Triton Industries, Inc.
7800 Northport Dr.
Lansing, MI 48917
517-322-3822

www.manitouboats.com



2013 Manitou 25 Oasis VP

BOAT	
2013 Manitou 25 Oasis VP	
Material:	Aluminum
Length:	26' 4"
Beam:	8' 6"
Weight w/o Engine:	3050 Lbs
Maximum HP:	150 HP
Fuel Capacity:	44 Gallons
Transom Height:	20" Shaft
Steering:	Hydraulic/Electric

ENGINE	
2013 Evinrude® 150 ETEC®	
Engine Type:	60° V6
Horsepower:	150 @ 5350 RPM
Displacement:	158 cu in
Induction:	ETEC DFI
Operating Range:	4850-5858 RPM
Weight:	418 LBS Dry Weight
Gear Ratio:	1.85:1

PROPELLER	
BRP™	
Material:	Aluminum
Diameter/Pitch:	15 x 15"
No. of Blades:	3
Part Number:	765186
MOUNTING HEIGHT	
Hole Position:	#1
Jack Plate:	N/A
AV Mounting:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	2.1	0.18	11.5	454
1000	4.3	0.50	8.7	344
1500	6.4	1.13	5.6	223
2000	8.1	1.77	4.6	181
2500	12.4	2.95	4.2	166
3000	16.2	4.41	3.7	145
3500	20.2	6.22	3.3	129
4000	23.6	7.89	3.0	118
4500	26.7	10.38	2.6	102
5000	29.6	12.96	2.3	90
5550	32.2	15.15	2.1	84
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Medium Chop
Wind Velocity:	10 MPH
Air Temperature:	85° F
Fuel Load:	Full
Weight:	1 Man, Fuel, Safety/Test Gear

PERFORMANCE SUMMARY
Top Speed: 32.2 MPH
Best Fuel Efficiency: 3.7 MPG with a range of 145 Miles @ 16.2 MPH
Acceleration: 3.0 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2010 BRP US Inc. All rights reserved.

™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

