

EVINRUDE

E-TEC

PERFORMANCE REPORT

BULLETIN #: 1200

BOAT TYPE: Pontoon

DATE OF TEST: 6/26/2016

ENGINE 1: C200XO / C200XC



BRP US, Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com

Manitou

Triton Industries, Inc.
16020 S. Lowell Rd.
Lansing, MI 48906
517-322-3822
www.manitoupontoonboats.com
2017 MANITOU 25 X-PLODE XT
SHP

BOAT

2017 MANITOU 25 X-PLODE XT SHP

Material	Aluminum
Length	26' 4"
Beam	8' 6"
Weight w/o Engine	3620 LBS
Maximum HP	600 HP
Fuel Capacity	90 Gallons
Transom Height	25"
Steering	I Dock

ENGINE

Evinrude® E-TEC® G2™ 200 HP

Engine Type	66° V-6
Horsepower	200
Displacement	167 cu in / 2.7L
Induction	E-TEC® D.I.
Operating Range	5000-6000 RPM
Weight	533 / 528 LBS Dry Weight
Gear Ratio	2.17:1

PROPELLER

Rebel™

Material	Stainless
Diameter/Pitch	14.875" / 22"
No. of Blades	3
Part Number	763996/763997
Prop Vent Hole	NA

MOUNTING HEIGHT

Hole Position	#2
Jack Plate	No
AV Mounting	0

PERFORMANCE DATA

RPM	MPH	GPH	MPG	RANGE
500	3.00	0.45	6.67	540
1000	5.00	1.10	4.55	368
1500	7.00	2.40	2.92	236
2000	11.00	4.40	2.50	203
2500	18.50	6.25	2.96	240
3000	13.25	8.75	1.51	123
3500	30.50	11.80	2.58	209
4000	37.00	15.30	2.42	196
4500	42.00	18.95	2.22	180
5000	46.00	21.60	2.13	173
5500	51.50	26.80	1.92	156
5725	53.00	34.25	1.55	125

TEST CONDITIONS

Water Conditions	Rough
Wind Velocity	10-15 MPH
Air Temperature	80° F
Fuel Load	full Gallons
Weight	2 Adults/safety equipment

PERFORMANCE SUMMARY

Top Speed	53 MPH
Best Fuel Efficiency	2.58 MPG For 209 Miles @ 30.50 MPH
Acceleration	3.6 seconds to plane

Fuel Data Range (Miles) Based On 90% Fuel Capacity



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2015 BRP US Inc. All rights reserved. ™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

EVINRUDE
E-TEC®

