



BULLETIN #: PE1035

ENGINE: E135HSLAA

BOAT TYPE: Aluminum

DATE OF TEST: 7/15/13



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com

MirroCraft

Northport Marine LLC
39 N. Harding Street
Gillett, WI 54124
920-855-2168
www.mirrocraft.com



2014 Mirrocraft 1766 Dual Impact

BOAT	
2014 Mirrocraft 1766 Dual Impact	
Material:	Aluminum
Length:	17' 3"
Beam:	93"
Weight w/o Engine:	1450 LBS Dry
Maximum HP:	150 HP
Fuel Capacity:	29 Gallons
Transom Height:	20" Shaft
Steering:	Hydraulic

ENGINE	
2014 Evinrude® 135 HO ETEC®	
Engine Type:	60° V6
Horsepower:	Factory Tuned
Displacement:	158 Cu.In.
Induction:	ETEC DFI
Operating Range:	5300-6000 RPM
Weight:	418 LBS Dry Weight
Gear Ratio:	1.85:1

PROPELLER	
BRP	
Material:	Aluminum
Diameter/Pitch:	14 1/2" x 19"
No. of Blades:	3
Part Number:	765188
MOUNTING HEIGHT	
Hole Position:	#1
Jack Plate:	N/A
AV Mounting:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	2.4	0.18	13.5	352
1000	4.8	0.62	7.7	202
1500	6.3	1.33	4.8	124
2000	7.1	2.88	2.5	65
2500	19.3	3.45	5.6	146
3000	25.1	4.75	5.3	138
3500	30.5	6.31	4.8	126
4000	35.2	7.95	4.4	116
4500	39.4	10.22	3.9	101
5000	44.8	12.04	3.7	97
5500	47.7	13.40	3.6	93
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Calm
Wind Velocity:	5 MPH
Air Temperature:	91° F
Fuel Load:	6 Gallons
Weight:	2 Men, Fuel, Safety/Test Gear

PERFORMANCE SUMMARY	
Top Speed:	47.7 MPH
Best Fuel Efficiency:	5.6 MPG with a range of 146 Miles @ 19.3 MPH
Acceleration:	3.15 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2010 BRP US Inc. All rights reserved.

™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

