



BULLETIN#: PE932

ENGINE: DE300PX/DE300CX

BOAT TYPE: Pontoon

DATE OF TEST: 8/10/12



Bombardier Recreational Products Inc. 10101 Science Drive Sturtevant, WI 53177 www.evinrude.com



Premier Marine Inc. 26612 Fallbrook Ave. Wyoming, MN 55092 1-800-815-6392

www.pontoon.com



2013 Premier 290 GrandView PTX

BOAT				
2013 Premier 290 Grandview PTX				
Material:	Aluminum			
Length:	31' 4"			
Beam:	10'			
Weight w/o Engine:	4175 LBS Dry			
Maximum HP:	600 HP			
Fuel Capacity:	80 gallons			
Transom Height:	25" Shaft			
Steering:	Hydraulic/Electric			

ENGINE				
Twin 2013 Evinrude® ETEC® 300				
90° V6				
300HP @ 5500 RPM				
3.4 litre				
ETEC DFI				
5000-6000 rpm				
534 LBS Dry Weight				
1.85:1				

PROPELLER			
BRP Rebel™			
Material:	Stainless Steel		
Diameter/Pitch:	15 3/8" x 18"		
No. of Blades:	3		
Part Number:	763988/763989		
MOUNTING HEIGHT			
Hole Position:	#2		
Jack Plate:	N/A		
Motor Height	N/A		

PERFORMANCE DATA					
RPM	MPH	GPH	MPG	RANGE	
500	3.1	0.35	8.9	638	
1000	5.9	1.30	4.5	327	
1500	8.0	2.80	2.9	206	
2000	12.8	5.00	2.6	184	
2500	19.8	11.00	1.8	129	
3000	25.4	13.90	1.8	131	
3500	29.5	17.20	1.7	123	
4000	34.7	21.40	1.6	117	
4500	40.5	26.45	1.5	110	
5000	44.5	34.90	1.3	92	
5500	48.8	46.15	1.1	76	
5900	52.5	50.95	1.0	74	
Range (Miles) Based On 90% Fuel Capacity					

TEST CONDITIONS		
Water Conditions:	Medium Chop	
Wind Velocity:	15 MPH	
Air Temperature:	85° F	
Fuel Load:	Full	
Weight:	1 Man, Fuel, test & safety gear	
	Water Conditions: Wind Velocity: Air Temperature: Fuel Load:	

PERFORMANCE SUMMARY

Top Speed: 52.5 MPH

Best Fuel Efficiency: 1.8 MPG with a range of 131 Miles @

25.4 MPH

Acceleration: 2.5 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2010 BRP US Inc. All rights reserved.



