



BULLETIN#: PE1085

ENGINE: E250DPX

BOAT TYPE: Pontoon

DATE OF TEST: 10/13/13



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



Nauti Global Group
4500 Middlebury Street
Elkhart, IN 46516
574-522-8381
www.nauticglobalgroup.com



2014 Sanpan 2500 WB

BOAT	
2014 Sanpan 2500 WB	
Material:	Aluminum
Length:	26' 10"
Beam:	8' 6"
Weight w/o Engine:	3573 LBS Dry
Maximum HP:	350 HP
Fuel Capacity:	45 gallons
Transom Height:	25" Shaft
Steering:	Hydraulic/Electric

ENGINE	
Evinrude® ETEC® 250HP	
Engine Type:	90° V6
Horsepower:	250 @ 5150 RPM
Displacement:	3.3 litre
Induction:	ETEC DFI
Operating Range:	5250-6000 rpm
Weight:	524 LBS Dry Weight
Gear Ratio:	1.85:1

PROPELLER	
BRP Rebel™	
Material:	Stainless Steel
Diameter/Pitch:	15 3/4" x 15"
No. of Blades:	3
Part Number:	763984
MOUNTING HEIGHT	
Hole Position:	#2
Jack Plate:	N/A
Motor Height	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	2.0	0.26	7.7	312
1000	4.4	0.60	7.3	297
1500	6.3	1.65	3.8	153
2000	7.5	2.80	2.7	108
2500	12.8	5.15	2.5	101
3000	17.4	7.05	2.5	100
3500	22.0	8.50	2.6	105
4000	27.8	10.85	2.6	104
4500	32.0	12.70	2.5	102
5000	36.4	16.15	2.3	91
5500	40.5	19.50	2.1	84
5775	42.6	22.50	1.9	77
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	calm
Wind Velocity:	5 MPH
Air Temperature:	80° F
Fuel Load:	1/2 Full
Weight:	2 Men, Fuel, test & safety gear

PERFORMANCE SUMMARY	
Top Speed:	42.6 MPH
Best Fuel Efficiency:	2.6 MPG with a range of 105 Miles @ 22 MPH
Acceleration:	3.26 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2013 BRP US Inc. All rights reserved.

™ and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

